

Outdoor unit	RXA20A2V1B
Indoor unit	FTXA20A2V1BS

<b>Function</b>		<b>Heating season</b>	
Cooling	Yes	Average (mandatory)	Yes
Heating	Yes	Warmer (if designated)	Yes
		Colder (if designated)	No

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Design Load</b>				<b>Seasonal efficiency</b>			
Cooling	Pdesignc	2.00	kW	Cooling	SEER	8.75	-
heating / Average	Pdesignh	2.40	kW	heating / Average	SCOP / A	5.15	-
heating / Warmer	Pdesignh	1.75	kW	heating / Warmer	SCOP / W	6.26	-
heating / Colder	Pdesignh		kW	heating / Colder	SCOP / C		-

Declared capacity* for cooling, at indoor temperature 27(19) °C and outdoor temperature Tj				Declared energy efficiency ratio*, at indoor temperature 27(19) °C and outdoor temperature Tj			
Tj = 35°C	Pdc	2.00	kW	Tj = 35°C	EERd	4.70	-
Tj = 30°C	Pdc	1.47	kW	Tj = 30°C	EERd	6.96	-
Tj = 25°C	Pdc	0.95	kW	Tj = 25°C	EERd	10.37	-
Tj = 20°C	Pdc	1.27	kW	Tj = 20°C	EERd	16.36	-

Declared capacity* for heating / Average season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance* / Average season, at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7°C	Pdh	2.12	kW	Tj = -7°C	COPd	3.56	-
Tj = 2°C	Pdh	1.29	kW	Tj = 2°C	COPd	5.24	-
Tj = 7°C	Pdh	0.92	kW	Tj = 7°C	COPd	6.27	-
Tj = 12°C	Pdh	1.10	kW	Tj = 12°C	COPd	8.05	-
Tj = bivalent temperature	Pdh	2.12	kW	Tj = bivalent temperature	COPd	3.56	-
Tj = operating limit	Pdh	2.31	kW	Tj = operating limit	COPd	2.48	-

Declared capacity* for heating / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance* / Warmer season, at indoor temperature 20 °C and outdoor temperature Tj			
Tj = 2°C	Pdh	1.75	kW	Tj = 2°C	COPd	4.76	-
Tj = 7°C	Pdh	1.16	kW	Tj = 7°C	COPd	6.15	-
Tj = 12°C	Pdh	1.1	kW	Tj = 12°C	COPd	8.05	-
Tj = bivalent temperature	Pdh	1.75	kW	Tj = bivalent temperature	COPd	4.76	-
Tj = operating limit	Pdh		kW	Tj = operating limit	COPd	2.48	-

Declared capacity* for heating / Colder season, at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance* / Colder season, at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7°C	Pdh		kW	Tj = -7°C	COPd		-
Tj = 2°C	Pdh		kW	Tj = 2°C	COPd		-
Tj = 7°C	Pdh		kW	Tj = 7°C	COPd		-
Tj = 12°C	Pdh		kW	Tj = 12°C	COPd		-
Tj = bivalent temperature	Pdh		kW	Tj = bivalent temperature	COPd		-
Tj = operating limit	Pdh		kW	Tj = operating limit	COPd		-
Tj = -15°C	Pdh		kW	Tj = -15°C	COPd		-

Bivalent temperature				Operating limit temperature			
heating / Average	Tbiv		°C	heating / Average	Tol	-15	°C
heating / Warmer	Tbiv	2	°C	heating / Warmer	Tol		°C
heating / Colder	Tbiv		°C	heating / Colder	Tol		°C

Cycling interval capacity				Cycling interval efficiency			
for cooling	Pcycc		kW	for cooling	EERcyc		-
for heating	Pcych		kW	for heating	COPcyc		-
Degradation co-efficient cooling**	Cdc	0.25	-	Degradation co-efficient cooling**	Cdh	0.25	-

Electric power input in power models other than 'active mode'				Annual electricity consumption			
off mode	Poff	5.0E-4	kW	Cooling	QCE	80	kWh/a
standby mode	Psb	5.0E-4	kW	heating / Average	QHE	653	kWh/a
thermostat-off mode	Pto	0.007	kW	heating / Warmer	QHE	392	kWh/a
crankcase heater mode	PCK	0.0	kW	heating / Colder	QHE		kWh/a

Capacity control				Other items			
fixed	N			Sound power level (indoor/outdoor)	LWA	57 / 59	db(A)
staged	N			Global warming potential	GWP	675.0	kgCO <sub>2</sub> eq.
variable	N			Rated air flow (indoor/outdoor)	-	11.0 / 34.0	m <sup>3</sup> /min

<b>Contact details for obtaining more information</b>	<b>DAIKIN EUROPE N.V.</b> Zandvoordestraat 300 B-8400 Oostende Belgium
---	---

\* for staged capacity units, two values divided by a slash (/) will be declared in each box in the section 'Declared capacity of the unit' and 'Declared EER/COP' of the unit.  
 \*\* if default Cd = 0.25 is chosen then (results from) cycling tests are not required. Otherwise either the heating of cooling cycling test value is required.